



Familia de emportables LED orientables con movimiento cardánico, baffle antideslumbrante y fuente de luz recedida. Versiones con marcos redondo y cuadrado.



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
14W	24°	2700K	920lm	65.7 lm/W	TRIAC	BUILT IN	06.AA28.2020.03
					TRIAC	BUILT IN	06.AA28.2020.06
		3000K	960lm	68.6 lm/W	TRIAC	BUILT IN	06.AA28.3020.03
	38°	2700K	983lm	70.2 lm/W	TRIAC	BUILT IN	06.AA28.3020.06
					TRIAC	BUILT IN	06.AA28.2030.03
		3000K	TRIAC	BUILT IN	06.AA28.2030.06		
					TRIAC	BUILT IN	06.AA28.3030.03
					TRIAC	BUILT IN	06.AA28.3030.06

INFORMACIÓN TÉCNICA


CRI	>80
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

INFORMACIÓN GENERAL

USO	
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø90x99mm
CUT OUT	Ø84mm
PESO (KG)	0.26
REGULACIÓN	
COLOR	Blanco Texturado - Negro Texturado



CREE ⇄



CURVAS FOTOMÉTRICAS

DUORO R 14W

