




Novedosa familia de empotrables con cabezales cilíndricos extraíbles, de diseño sobrio y minimalista



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
12W	15°	2700K	725lm	60.41 lm/W	TRIAC	EXTERNO TCI	06.78.1121.03
					TRIAC	EXTERNO TCI	06.78.1121.06
		3000K			TRIAC	EXTERNO TCI	06.78.1118.03
					TRIAC	EXTERNO TCI	06.78.1118.06
	22°	2700K			TRIAC	EXTERNO TCI	06.78.1122.03
					TRIAC	EXTERNO TCI	06.78.1122.06
		3000K			TRIAC	EXTERNO TCI	06.78.1119.03
					TRIAC	EXTERNO TCI	06.78.1119.06
	38°	2700K			TRIAC	EXTERNO TCI	06.78.1123.03
					TRIAC	EXTERNO TCI	06.78.1123.06
		3000K			TRIAC	EXTERNO TCI	06.78.1120.03
					TRIAC	EXTERNO TCI	06.78.1120.06

INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

INFORMACIÓN GENERAL

USO	Interior
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø100x105mm
CUT OUT	Ø90x120mm
PESO (KG)	
REGULACIÓN	Basculación 90° / Giro 360° / Extraíble
COLOR	Blanco Texturado - Negro Texturado



bridgelux.



CURVAS FOTOMÉTRICAS

SHHH 12W UNI

