


Novedosa familia de empotrables con cabezales cilíndricos extraíbles, de diseño sobrio y minimalista



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
8W	15°	2700K	900lm	112.5 lm/W	TRIAC	EXTERNO	06.78.1133.03
					TRIAC	EXTERNO	06.78.1133.06
		3000K			TRIAC	EXTERNO	06.78.1130.03
					TRIAC	EXTERNO	06.78.1130.06
	24°	2700K			TRIAC	EXTERNO	06.78.1134.03
					TRIAC	EXTERNO	06.78.1134.06
		3000K			TRIAC	EXTERNO	06.78.1131.03
					TRIAC	EXTERNO	06.78.1131.06
	38°	2700K			TRIAC	EXTERNO	06.78.1135.03
					TRIAC	EXTERNO	06.78.1135.06
		3000K			TRIAC	EXTERNO	06.78.1132.03
					TRIAC	EXTERNO	06.78.1132.06

INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

INFORMACIÓN GENERAL

USO	Interior
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	150x75mmx151mm
CUT OUT	145x70mm
PESO (KG)	0.55
REGULACIÓN	Basculación 90° / Giro 360° / Extraíble
COLOR	Blanco Texturado - Negro Texturado



bridgelux.

