


SHHH 8W MINI UNI

Novedosa familia de empotrables con cabezales cilíndricos extraíbles, de diseño sobrio y minimalista



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código	
8W	15°	2700K	450lm	56.25 lm/W	TRIAC	EXTERNO	06.78.1103.03	
					TRIAC	EXTERNO	06.78.1103.06	
		3000K			TRIAC	EXTERNO	06.78.1100.03	
	24°				TRIAC	EXTERNO	06.78.1100.06	
		2700K			TRIAC	EXTERNO	06.78.1104.03	
					TRIAC	EXTERNO	06.78.1104.06	
	38°				TRIAC	EXTERNO	06.78.1101.03	
		2700K			TRIAC	EXTERNO	06.78.1101.06	
					TRIAC	EXTERNO	06.78.1105.03	
					2700K	TRIAC	EXTERNO	06.78.1105.06
					3000K	TRIAC	EXTERNO	06.78.1102.03
						TRIAC	EXTERNO	06.78.1102.06

INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	220-240

INFORMACIÓN GENERAL

USO	Interior
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø75x91mm
CUT OUT	Ø70x110mm
PESO (KG)	0.26
REGULACIÓN	Basculación 90° / Giro 360° / Extraíble
COLOR	Blanco Texturado - Negro Texturado



bridgelux.



CURVAS FOTOMÉTRICAS

SHHH 8W MINI UNI

